

SHOWER

Model: CC1251

- ABS Plastic Bowl
- ABS Plastic Shower Head



The Cascaide™ Shower/Eyewash Unit

introduces a quality product at a competitive price. This economical unit complies to the ANSI Z358.1 performance standard, is packaged for quick and easy assembly and comes with the floor flange mounting plate for freestanding installation. The highly visible UV resistant ABS plastic yellow showerhead along with the ABS Yello-Bowl® ensure that it can be easily seen by a person in need. The eyewash heads are manufactured of solvent resistant yellow acetal and have integral hinged covers to shield them from dust and dirt when not in use, and to enable them to open automatically when water is flowing. Variable positions for the water inlet allow for more installation options. The showerhead delivers a minimum of a 20" (50.8cm) diameter pattern to the target area 60" (152.4cm) above standing level. When properly installed, the emergency shower and eyewash station will provide a non-injurious stream of water for 15 minutes.

MODEL DESCRIPTION

MODEL	DESCRIPTION
CC1251	20 gpm combination shower and eyewash unit
CC2251	30 gpm combination shower and eyewash unit



Every model in this section includes 7" x 11" sign (17.8 cm x 27.9 cm)


PRODUCT FEATURES

- ANSI Z358.1 Compliant
- Sch. 40 hot dipped galvanized steel pipe
- 20 gpm or 30 gpm showerhead @ 30/70 PSI
- 2.4 gpm eyewash @ 30/70 PSI
- 1-1/4" NPT Supply
- 1-1/4" NPT Waste



Encon Safety Products
Sam Houston Pkwy. N.
Houston, Texas 77041

CASCAIDE™ SHOWER/EYEWASH WITH STAINLESS STEEL BOWL & SHOWERHEAD



CASCAIDE™

The Cascaide™ Shower/Eyewash Unit introduces a quality product at a competitive price. This economical unit complies to the ANSI Z358.1 performance standard, is packaged for quick and easy assembly and comes with the floor flange mounting plate for freestanding installation. It is available with a Stainless Steel bowl and shower head, constructed of 304 stainless steel, to promote the safe, long life of your station and to provide you with more choices in safety equipment for your facility. The eyewash heads have integral hinged covers to shield them from dust and dirt when not in use, and to enable them to open automatically when water is flowing. Variable positions for the water inlet allow for more installation options. The showerhead delivers a minimum of a 20" (50.8cm) diameter pattern to the target area 60" (152.4cm) above standing level. When properly installed, the emergency shower and eyewash station will provide a non-injurious stream of water for 15 minutes.

SHOWER

Model: CC3261

- Stainless Steel Bowl
- Stainless Steel Shower Head



MODEL DESCRIPTION

Stainless steel bowl and showerheads


- | | |
|---------------|---|
| CC3261 | 20 gpm combination shower and eyewash unit with SS bowl and SS showerhead |
| CC4261 | 30 gpm combination shower and eyewash unit with SS bowl and SS showerhead |

Stainless steel bowl and ABS showerheads

- | | |
|---------------|--|
| CC1261 | 20 gpm combination shower and eyewash unit with SS bowl and ABS showerhead |
| CC2261 | 30 gpm combination shower and eyewash unit with SS bowl and ABS showerhead |

PRODUCT FEATURES

- ANSI Z358.1 Compliant
- Sch. 40 hot dipped galvanized steel pipe
- 20 gpm or 30 gpm showerhead @ 30/70 PSI
- 2.4 gpm eyewash @ 30/70 PSI
- 1-1/4" NPT Supply
- 1-1/4" NPT Waste



Every model in this section includes 7" x 11" sign (17.8 cm x 27.9 cm)



CASCAIDE™

Encon Safety Products
Sam Houston Pkwy. N.
Houston, Texas 77041